

**NO. 955  
RAIN SENSE**



No automatic system is complete without the Rain Sense. The Weathermatic Rain Sense acts as a switch to break the circuit to the solenoids during rainfall. The controller program continues to advance but the valves do not open. Maintenance-free unit features hygroscopic disks which absorb water and then dry at a rate similar to the landscape.

- Five year warranty
- Select 1/8, 1/4, 1/2, 3/4 or 1 inch rainfall for automatic system shutdown
- Vent ring adjustment to determine reset time
- Includes mounting kit with screw bracket and thumbscrew for gutter mount, and 25 feet of connection wire
- 24 V a.c.

**NO. 952  
PUMP CIRCUIT ACCESSORY PACKAGE**

- Remote pump start relay for use with controllers which do not have internal pump circuits
- U.L. listed rain-proof, gray PVC housing with gasket seal
- Two 1/2 in. conduit openings; plug-in type relay
- Housing dimensions: 4 in. x 4 in. x 2 in. (10,2 cm x 10,2 cm x 5 cm)



**ELECTRICAL**

Input from controller	24V a.c., 50/60 Hz/.050A;
Pump circuits contacts	250V a.c., 50/60 Hz/300VA

**NO. 954  
NI-CAD ADAPTER KIT**

For use with LMC Controllers (all models). Replaces standard alkaline battery back-up. Fully charges NiCad battery in 4 hours and fully-charged battery will back-up LMC for 24 hours minimum (battery not included).

**LMSP PEDESTAL**



- For LMC Series
- Heavy gauge stainless steel
- Low profile. Dimensions: 10 5/8 in. W x 32 1/4 in. H x 2 3/4 in. D (27 cm x 82 cm x 7 cm)
- Front access panel is 7 1/2 in. wide (19 cm wide)
- Pedestal fastens to 4 bolts (not included)
- Housing attachments included
- Order pedestal separately
- Specify **LMSP**

**VACP PEDESTAL**



- For VAC Controllers
- Heavy gauge steel with corrosion resistant polyester coating; large access door for wiring
- Hardware included
- Dimensions: 16 in. W x 20 in. H x 6 in. D (40,6 cm x 50,8 cm x 15,2 cm)
- Specify **VACP**

**MRMP PEDESTAL**



- For SL Series
- Construction: heavy gauge welded steel
- Finish: corrosion resistant polyester coating
- Functional design: low-profile height blends with landscape aesthetics, permits installation or maintenance technician to work sitting down; functional design makes wiring easy in a space 10 in. wide, 24 in. high, and 7 in. deep (25 cm x 61 cm x 18 cm)
- Vandal-resistant 7 in. (17,8 cm) wide front access panel is locked in place by the controller housing door
- Pedestal fastens to four bolts (not included); housing attachments are included
- Order pedestal separately
- Specify **MRMP**