



## Professional Spray Sprinklers for commercial and residential turf and groundcover applications

### LX SERIES

#### FEATURES

- Pressure-activated wiper seal for reliability
- Easy grip threaded cover
- Stainless steel retract spring
- High-strength ribbed design

#### QUICK INSTALLATION

- T-Plug™ Flush Cap on every head
- Side and bottom inlets on LX6 and LX12\*
- Ratchet nozzle alignment

\*Side inlet installation on LX6 and LX12 is not recommended in freezing climates.

#### NOZZLES

- Completely compatible with all industry-standard female thread nozzles
- LX MPR nozzles
- LX Adjustable Arc nozzles
- B Series brass nozzles  
*(Order nozzles separately)*

#### OPERATING DATA

- Pressure range: 15 to 70 psi (1,0 to 4,8 bars)
- Flow-by: Zero at 5 psi (0,3 bars) or greater
- Factory installed check valve: 9.5 ft/hd at 18 psi (2.9 m/hd at 1,2bar). Specify: LX4-CV, LX6-CV or LX12-CV

### LXS SHRUB ADAPTER



- 1/2 inch female inlet threads
- Durable plastic construction
- Top threads accept LX MPR nozzles, LX Adjustable Arc nozzles, B Series brass nozzles and all industry standard female thread nozzles
- Accepts LX nozzle protective screen (shipped with nozzle)