



COLEMANCABLE

Toll-Free (800) 323-9355

Wiring The World

Fax: (847) 689-1192


PRODUCT DATA SHEET

PART NUMBER: 54536
DESCRIPTION: 18/12 SOLID UNDERGROUND SPRINKLER SYSTEM WIRE
CONSTRUCTION: This cable consists of twelve bare copper insulated conductors with an overall jacket.
APPROVALS: Underwriters Laboratory - Underground Golf Course Sprinkler System Cable
APPLICATION: Underground Sprinkler Systems

Construction Parameters:

Conductor	18 AWG Bare Copper
Stranding	Solid
Insulation Material	Polypropylene
Insulation Thickness	0.016" Nom.
Insulated Conductor Diameter	0.072" Nom.
Number of Conductors	12
Lay Length	Parallel
Jacket Material	PVC
Jacket Thickness	0.026" Nom.
Overall Cable Diameter	0.352" Nom.
Approximate Cable Weight	93.0 Lbs/1M' Nom.
Flame Rating	VW-1 or FT1 Verticle Flame Test

Cable Cross-Section



Electrical & Enviromental Properties:

Temperature Rating	-20°C to 60°C
Operating Voltage	30 Volts RMS Max.
Capacitance Between Conductors @ 1 KHz	16 pF/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	-----
DC Resistance per Conductor @ 20°C	6.32 Ohms/1M' Nom.

Insulation Colors	Red White Green Blue Yellow Brown Orange Black Pink Gray Tan Purple
Jacket Color	Black (Other colors available for minimum order)

Legend (Surface Ink Print)	BARON WIRE E54868-B 18 AWG BAROGATION 30V SPRINKLER SYSTEMS WIRE (UL) DIRECT BURIAL
----------------------------	---

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.
 The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name _____

Customer Approval _____

Specification Issue Date: September 5, 2000